

# Curtain Outdoor Jeweller

Wireless dual technology curtain motion detector for outdoor and indoor use











# Advanced detection

- Two IR and one microwave sensors
- Motion detection range adjusted with a slider at the device enclosure
- Vertical viewing angle: 85° without blind spots under the detector¹
- Horizontal viewing angle: 8°




## Smart features

- Installing the detector perpendicular or parallel to the surface with SmartBracket or angle mount
- Pet immunity: the device ignores pets below 100 cm in height



## Eliminating false alarms

- IR sensors alarm verification with a Ka-band microwave sensor
- Three sensitivity levels: selectable in the app
- SmartDetect and dual technology motion detection algorithms for false alarms prevention
- Temperature compensation for effective motion detection at temperatures from -25 °C to +60 °C



## Jeweller and Wings

wireless communication

- Wireless communication range: up to 1,700 m
- Block cipher encryption for advanced data protection
- Regular polling to check the current state of the device
- Frequency hopping to prevent interception and jamming



# Sabotage protection

- Anti-masking system that meets the Grade 2 requirements<sup>2</sup>
- Tamper alarm and a built-in accelerometer to notify of an attempt to dismantle the device
- Protection against spoofing with device authentication
- Holding screw to secure the detector on SmartBracket



### Hassle-free installation

- Pairing with the hub by scanning the QR code
- Remote control and configuration in Ajax apps
- Calculated battery life: up to 3 years
- No need to disassemble the enclosure during the installation
- Bundled hood to protect from rain and snow

**Superior, Fibra,** and **Baseline** product lines are mutually compatible. This opens up numerous possibilities for building systems of any configuration.

Compliance with standards	Compatibility	Communication with a hub	Detection
EN 50131 (Grade 2) PD 6662:2017	Hubs Hub 2 (2G) Jeweller Hub 2 (4G) Jeweller Hub 2 Plus Jeweller Hub BP Jeweller Hub Hybrid (2G) Hub Hybrid (4G)  Range extenders ReX 2 Jeweller	Jeweller communication technology  Wings communication technology  Communication range up to 1,700 m In an open space  Frequency bands 866.0–866.5 MHz 868.0–868.6 MHz 868.7–869.2 MHz 905.0–926.5 MHz 915.85–926.5 MHz 921.0–922.0 MHz Depends on the sales region	Motion detection distance up to 8–12 m (when installed at a height of 1–2.4 m)  Motion detection angles vertical: 85° (15° when installed at a height of 1 m) horizontal: 8°  Motion detection speed 0.3 to 2.0 m/s The direction of the detector lens should be perpendicular to an alleged intrusion path into the facility.
Power supply Battery	Enclosure Color	Installation Operating temperature range	Complete set  Curtain Outdoor Jeweller
2 × CR123A (pre-installed) Calculated battery life up to 3 years	Dimensions  141 × 60 × 72 mm  (without angle mount)  141 × 76 × 84 mm  (with angle mount)  Weight  223 g  (without angle mount)  257 g	from -25 °C to +60 °C  Operating humidity up to 95%  Protection class IP55  Installation height 2.4 m (1 m when pet immunity is enabled)	SmartBracket mounting panel Hood 2 × CR123A battery (pre-installed) Angle mount Installation kit Quick start guide

<sup>1</sup> 15° when installed at a height of 1 m.

<sup>2</sup> The device recognizes anti-masking only for IR sensors. Masking detection for microwave sensors is not supported.











